

Digital Rotator

The Serology Rotator is designed to give years of dependable service, even in the busiest laboratory. It's the ideal space-saving instrument for procedures that require constant or timed rotation (mixing) such as RPR, VDRL, latex tests and for procedures that require a nonstandard speed.

FEATURES

- Widely used in VDRL, RPR, and EIA tests
- Stable and quiet operation
- Clear humidity tray
- Variable speed, timer control, and continuous operation

SPECIFICATIONS

- Speed: 20-240rpm
- Timer: 99 hours and 99 minute digital timer
- Power supply: AC 110V 60Hz
(220V 50/60Hz available)
- Load capacity: 4.4lbs at 20-150rpm
2.2lbs at 151-240rpm

WEIGHT AND DIMS

- Platform: 9 x 9in (230 x 230mm)
- Orbit diameter: 0.8in
- Weight: 8.6 lbs (3.9kgs)
- Width: 10in
- Depth: 12in
- Height: 5.5in



Digital Rotator

| Model # | Description |
|---------------|----------------------|
| RTL-BLVD-24T1 | 110v Digital Rotator |
| RTL-BLVD-24T2 | 220v Digital Rotator |



P 770.270.1394
F 770.270.2389

865 Marathon Parkway
Lawrenceville GA 30046

LWScientific.com